MICROCONTAMINATION CONTROL

GateKeeper[®] GPU 500 4R Gas Purifiers

Superior purity control


Entegris' GateKeeper® GPU gas purifiers were designed to improve purity consistency, lifetime and final purity. Leveraging its expertise in material science, Entegris has developed a new generation of purification products that deliver unsurpassed value and performance. The model 500 is designed for peak flow rates up to 75 slpm.



FEATURES & BENEFITS

Process control and protection	Purity control to ppt levels	
	Low pressure drop across the purifier	
	CE certified to the Pressure Equipment Directive (PED) and manufactured in an ISO® 9001:2000 facility	
Cost effective	Regenerable – eliminates disposal issues and costs	
	Long lifetime – improved cost of ownership	
Safe and simple to use	Use ambient temperature purification – no heat or power required to operate	
	Insensitive to orientation (horizontal/vertical)	

PERFORMANCE DATA



*The flow rate displayed on this graph may exceed maximum flow rate specification of the purifier model referenced in this data sheet. Please refer to maximum flow rate in the specifications section of this data sheet.

Note: Pressure drop may vary depending on media type.



SPECIFICATIONS

Materials of construction (housing)	316L stainless steel, electropolished	
Particle filtration type	Wafergard® – 316L stainless steel membrane	
Particle retention	Up to 3 LRV* for particles larger than 0.003 μm	
Filtration removal rating	≥0.003 µm	
Operating temperature	0-65°C (32-149°F)	
Fitting size and type	¹ /4" gasket seal**	
Fitting configuration	Male-to-male	
Operating pressure	1.01 barg-41.3 barg (0 psig-600 psig)	
Maximum flow rate	75 slpm	
Leak rating	1 × 10 ⁻⁹ atm cc/sec	
Dimensions	201.7 mm (7.94") × Ø76 mm (3")	
Approximate weight	1.8 kg (4 lbs)	

*Referenced as most penetration particle size.

**Also referred to as VCR[®] or face seal.

AVAILABLE MEDIA

Media	Gases purified	Contaminants removed	Outlet purity	Nominal flow rate ³
DZ	CO ₂	Volatile acids	<1 ppt	14 slpm
		Volatile bases	<1 ppt	
		Refractories	<1 ppt	
		Condensable organics	<1 ppt	
		H ₂ O	<1 ppb	
		O ₂	<200 ppt	
	H_2 , N_2 , Noble gases, H_2/N_2 , $H_2/Noble gases$	H ₂ O, CO ₂	<100 ppt in H_{2} and N_{2}	26 slpm
		O ₂	${<}250$ ppt in ${\rm H_2}$ and ${\rm N_2}$	
		СО	<1 ppb in HH $_{\rm 2}$ and N $_{\rm 2}$	
		CxHy (45–100 amu)	<10 ppt	
		CxHy (>100 amu)	<1 ppt	
		Refractory compounds (as HMDSO)	<1 ppt	

AVAILABLE MEDIA (CONTINUED)

Media	Gases purified	Contaminants removed	Outlet purity	Nominal flow rate ³
ΗX	H ₂ , N ₂ , Noble gases, H ₂ /N ₂ , H ₂ /Noble gases	H ₂ O, O ₂ , CO, CO ₂	<100 ppt in $\rm H_2$ and $\rm N_2$	26 slpm
IX –	N ₂ , Noble gases	H ₂ O, O ₂ , CO, CO ₂ , H ₂	<100 ppt in Ar and N ₂ 1	13 slpm
	Freon ¹ 13, 14, 23, 41, 116, 218	H ₂ O, O ₂		
NX	02	CO2	<1 ppb	32 slpm
		H ₂ O	<1 ppb	
OP (CDA, N ₂ , Noble gases	H ₂ O	<100 ppt in N ₂	27 slpm
		Condensable organics (as Toluene)	<1 ppt	
		Non-condensable organics² (as Butane)	<5 ppt	
		Refractory compounds (as HMDSO)	<1 ppt	
		Volatile acids (as SO ₂)	<1 ppt	
		Volatile bases (as NH ₃)	<10 ppt	
SX	NH ₃	H ₂ O	<2 ppb in NH_3	10.4 slpm
		CO2	<1 ppb	
		O ₂	<1 ppb	
		Hydrocarbons	<1 ppt	
ТХ	CDA, N ₂ , Noble gases, CO ₂ , NH ₃	Condensable organics (as Toluene)	<1 ppt	36 slpm⁴
		Non-condensable organics² (as Butane)	<5 ppt	
		Refractory compounds (as HMDSO)	<1 ppt	
WX	CDA, H ₂ , N ₂ , Noble gases, CO ₂ , NH ₃ , AsH ₃ , PH ₃ , GeH ₄ , SiH ₄	H ₂ O	<100 ppt in N ₂	108 slpm⁵
			<12 ppb in NH3	

¹ Removal of H₂O and O₂ only.

² Consult Entegris with specific non-condensable contaminants.


 3 With a 1 ppm H₂O impurity inlet challenge

⁴ With a 1 ppm Toluene impurity inlet challenge over 1 year

⁵ Lifetime will exceed 1 year at its maximum flow rate

ORDERING INFORMATION

GateKeeper 500 4R Gas Purifiers: part number



*Contact Entegris to determine if the purifier is designed for regeneration.

FOR MORE INFORMATION

Please call your Regional Customer Service Center today to learn what Entegris can do for you. Visit **entegris.com** and select the Contact Us link to find the customer service center nearest you.

TERMS AND CONDITIONS OF SALE

All purchases are subject to Entegris' Terms and Conditions of Sale. To view and print this information, visit **entegris.com** and select the Terms & Conditions link in the footer.



Corporate Headquarters 129 Concord Road Billerica, MA 01821 USA
 Customer Service

 Tel
 +1
 952
 556
 4181

 Fax
 +1
 952
 556
 8022

 Toll Free
 800
 394
 4083

Entegris[®], the Entegris Rings Design[™], Pure Advantage[™], and other product names are trademarks of Entegris, Inc. as listed on **entegris.com/trademarks**. All third-party product names, logos, and company names are trademarks or registered trademarks of their respective owners. Use of them does not imply any affiliation, sponsorship, or endorsement by the trademark owner. ©2015-2017 Entegris, Inc. | All rights reserved. | Printed in the USA | 4521-7889ENT-1117